

VRPRL 38


• DIMENSIONS (mm)



• HYDRAULIC DIAGRAM



• ASSEMBLY DIAGRAM



• DESCRIPTION

Direct control pressure adjustment valve with relieving and free return.

• OPERATION

Allows for free oil flow from E into U. When the pressure value set in U is achieved, the valve will shut the pass between E and U in order to maintain constant pressure in U. Should the pressure in U further exceed the setting value, the pass in E will shut and the connection in U will joint to Dr to relieve eventual pressure peaks. Single acting valve, allows for free oil return from U to E.

• PERFORMANCE

Maximum flow : 20 l/min.

Maximum Pressure:

- 210 bar (aluminium valve)
- 350 bar (steel valve)

Application range with standard springs:

- 5 ÷ 50 bar (test setting: 40 bar at 5 l/min.)
- 40 ÷ 110 bar (test setting: 90 bar at 5 l/min.)
- 100 ÷ 200 bar (test setting: 160 bar at 5 l/min.)

To perform setting of the valve see the pressure drop/ flow diagram.

Oil leak in Dr: 20 cc per minute at 150 bar pressure and oil viscosity 46 cSt.

Working temperature:


- min. -25°C max. 90°C with standard BUNA N gaskets
- min. -20°C max. 120°C with optional VITON gaskets

• RECOMMENDATIONS:

Fluid: best use mineral oil with viscosity ranging between 10 and 200 cSt.


Filter: see page Z.9000.000.
Weight: 0.85 kg and 1.73 kg for aluminium and steel valves respectively.
Material: internal components made out of high-grade steel duly treated and fabricated.
For more information please ask our technical office.
Variations and modifications of technical features and dimensions are reserved. **OLEOSTAR S.p.A.** also reserves the right to stop production of each and any model listed in the catalogue with no notice.
Copyrights on the text contained herein belong to **OLEOSTAR S.p.A.** . Partial and full reproductions or copies of this catalogue are forbidden.

• RATING DIAGRAMS



Oil viscosity 46 cSt

• ADJUSTMENTS



• CODE NUMBER

VRPRL 38 / □□ . □ / □□

Pressure settings (bar)	Adjustment	Body material
TB) 5÷50	**S**	**_** Aluminium
TV) 40÷110	**V**	**ac** Steel
TS) 100÷200	**W**	